



MADE IN ITALY



ACS - AFC - AFE CE - AFE/CAR SERIES

VASI DI ESPANSIONE CON MEMBRANA - EXPANSION TANKS WITH MEMBRANE
AUTOCLAVI CON MEMBRANA INTERCAMBIABILE - INTERCHANGEABLE MEMBRANE SURGE TANKS

INTERCHANGEABLE MEMBRANE SURGE TANKS



ACS 2



ACS 3-24

MODEL	Height mm	Ø mm	pmax bar	pprec bar	Temp °C	Membrane	Connection
ACS							
ACS 2	240	120	10	3,5	-10 +100	BUTYL	1/2"
ACS 3	245	170	10	2,5	-10 +100	BUTYL	3/4"
ACS 5	275	170	10	2,5	-10 +100	BUTYL	3/4"
ACS 5 d.160	315	160	10	2,5	-10 +100	BUTYL	3/4"
ACS CE 8	305	220	10	2,5	-10 +100	BUTYL	3/4"
ACS CE 12	315	260	10	2,5	-10 +100	EPDM	3/4"
ACS CE 16	350	260	8-10	2,5	-10 +100	EPDM	3/4"
ACS CE 18	380	260	8-10	2,5	-10 +100	EPDM	3/4"
ACS CE 24	490	260	8-10	2,5	-10 +100	EPDM	3/4"-1"
AS CE 24	365	350	8-10	2,5	-10 +100	EPDM	3/4"-1"



AFC 3-24



AF 24

MODEL	Height mm	Ø mm	pmax bar	pprec bar	Temp °C	Membrane	Connection
AFC							
AFC 3	245	170	10	1,5	-10 +100	EPDM	3/4"
AFC 5	275	170	10	1,5	-10 +100	EPDM	3/4"
AFC CE 8	305	220	10	1,5	-10 +100	EPDM	3/4"
AFC CE 12	315	260	10	1,5	-10 +100	EPDM	3/4"
AFC CE 16	350	260	8	1,5	-10 +100	EPDM	3/4"
AFC CE 18	380	260	8	1,5	-10 +100	EPDM	3/4"
AFC CE 24	490	260	8	1,5	-10 +100	EPDM	3/4"-1"
AF CE 24	365	350	8	1,5	-10 +100	EPDM	3/4"-1"



AFOSB 24

MODEL	Height mm	Ø mm	pmax bar	pprec bar	Temp °C	Membrane	Connection
AFOSB							
AFOSB CE 24	490	260	8	1,5	-10 +100	EPDM	3/4"-1"



AFESB

MODEL	Height mm	Ø mm	pmax bar	pprec bar	Temp °C	Membrane	Connection
AFESB							
AFESB CE 50	600	380	10	1,5	-10 +100	EPDM	1"
AFESB CE 60	690	380	10	1,5	-10 +100	EPDM	1"
AFESB CE 80	690	460	10	1,5	-10 +100	EPDM	1"
AFESB CE 100	780	460	10	2,5	-10 +100	EPDM	1"
AFESB CE 150	950	510	10	2,5	-10 +100	EPDM	1"
AFESB CE 200	1000	590	10	2,5	-10 +100	EPDM	1 1/4"
AFESB CE 300	1150	650	10	2,5	-10 +100	EPDM	1 1/4"
AFESB CE 500	1420	750	10	2,5	-10 +100	EPDM	1 1/4"



CAR 19

MODEL	Height mm	Ø mm	pmax bar	pprec bar	Temp °C	Membrane	Connection
CAR 19							
CAR 19	112	84	20	3,5	-10 +100	EPDM	1/2"-1/4"



AFE 50-500



AFE 750-2500



AFE 3000-5000

MODEL	Height mm	Ø mm	pmax bar	pprec bar	Temp °C	Membrane	Connection
AFE							
AFE CE 35	475	380	10	1,5	-10 +100	EPDM	1"
AFE CE 50	720	380	10	1,5	-10 +100	EPDM	1"
AFE CE 60	830	380	10	1,5	-10 +100	EPDM	1"
AFE CE 80	760	460	10	1,5	-10 +100	EPDM	1"
AFE CE 100	880	460	10	2,5	-10 +100	EPDM	1"
AFE CE 150	1030	510	10	2,5	-10 +100	EPDM	1"
AFE CE 200	1100	590	10	2,5	-10 +100	EPDM	1 1/4"
AFE CE 300	1280	650	10	2,5	-10 +100	EPDM	1 1/4"
AFE CE 500	1600	750	10	2,5	-10 +100	EPDM	1 1/4"
AFE CE 750	1850	800	10	2,5	-10 +100	EPDM	F 2"
AFE CE 750 d. 750	2045	750	8	2,5	-10 +50	EPDM	F 2"
AFE CE 1000	2130	800	10	2,5	-10 +50	EPDM	F 2 1/2"
AFE CE 1500	2130	1000	10	2,5	-10 +50	EPDM	F 2 1/2"
AFE CE 2000	2550	1100	10	2,5	-10 +50	BUTYL	DN 65
AFE CE 2500	2845	1100	10	2,5	-10 +50	BUTYL	DN 65
AFE CE 3000	2930	1250	10	2,5	-10 +50	BUTYL	DN 65
AFE CE 4000	3030	1450	10	2,5	-10 +50	BUTYL	DN 65
AFE CE 5000	3800	1450	10	2,5	-10 +50	BUTYL	DN 65



AFC/CAR

MODEL	Height mm	Ø mm	pmax bar	pprec bar	Temp °C	Membrane	Connection
AFC/CAR							
AFC/CAR CE 8	310	220	16-20	2,5	-10 +100	BUTYL	3/4"
AFC/CAR CE 12	315	265	16-20	2,5	-10 +100	BUTYL	3/4"
AFC/CAR CE 18	375	265	16-20	2,5	-10 +100	BUTYL	3/4"
AFC/CAR CE 24	490	265	16-20	2,5	-10 +100	BUTYL	3/4"



AFE/CAR

MODEL	Height mm	Ø mm	pmax bar	pprec bar	Temp °C	Membrane	Connection
AFE/CAR							
AFE/CAR CE 35	475	380	16	1,5	-10 +100	EPDM	1"
AFE/CAR CE 50	720	380	16	1,5	-10 +100	EPDM	1"
AFE/CAR CE 60	830	380	16	1,5	-10 +100	EPDM	1"
AFE/CAR CE 80	760	460	16	1,5	-10 +100	EPDM	1"
AFE/CAR CE 100	880	460	16	2,5	-10 +100	EPDM	1"
AFE/CAR CE 150	1030	510	16	2,5	-10 +100	EPDM	1"
AFE/CAR CE 200	1100	590	16	2,5	-10 +100	EPDM	1 1/4"
AFE/CAR CE 300	1280	650	16	2,5	-10 +100	EPDM	1 1/4"
AFE/CAR CE 500	1600	750	16	2,5	-10 +100	EPDM	1 1/4"